

Made in Japan

Japan Quality

AUTOBACS fully synthetic engine oils meet the latest specifications required by car manufacturers to provide superior engine protection and deliver improved fuel economy with a cleaner engine. With over 45 years automotive industry experience, AUTOBACS is the trusted name for all your motoring needs. Let AUTOBACS engine oils enrich your driving experience with the spirit of Japanese quality and reliability. AUTOBACS is Japan Quality.





SP - The New Engine Oil Standard

AUTOBACS API SP engine oils are certified to the latest SP engine oil standards to protect against low speed pre-ignition (LSPI), provide enhanced timing chain wear protection and deliver even better fuel efficiency. Made in Japan, this all new range of fully synthetic SP engine oils are the next level choice for drivers who want only the best performance for their cars.

- Protection against Low Speed Pre-Ignition (LSPI)
- Enhanced Timing Chain Wear Protection
- Improved Fuel Efficiency
- Improved Engine Cleaning and Oxidative Stability



AUTOBACS Fully Synthetic Engine Oil

0W-16 SP/GF-6B

API licensed & ILSAC certified, this high performance oil provides superior engine protection while delivering improved fuel economy & engine cleaning. Recommended for next generation fuel efficient engines including hybrid & idling stop vehicles.

Oil type	
Pour point (°C)	
Flash point (℃)	
40℃	37.0
100℃	7.26
Viscosity index	
	(°C) 40°C 100°C



OW-20 SP/GF-6A

API licensed & ILSAC certified, this high performance oil provides superior engine protection while delivering improved fuel economy & engine cleaning. Recommended for a wide range of fuel efficient gasoline engines including hybrid & idling stop vehicles.

Oil type		Fully-Synthetic
Pour point (°C)		- 45.0
Flash point (℃)		238
Kinematic viscosity (mm²/s)	40℃	44.14
	100℃	8.47
Viscosity index		172



OW-30 SP/GF-6A

API licensed & ILSAC certified, this high performance oil is made with Poly Alpha Olefin (PAO) for superior cold-start & high temperature resistance. Recommended for gasoline engines including turbocharged vehicles where either OW-30 or OW-20 is specified.

Oil type		Fully-Synthetic
Pour point (℃)		- 45.0
Flash point (°C)		232
Kinematic viscosity (mm²/s)	40°C	53.56
	100℃	9.91
Viscosity index		174



5W-30 SP/CF/GF-6A

API licensed & ILSAC certified, this high performance oil provides superior engine protection while delivering improved fuel economy & engine cleaning. Recommended for both gasoline & diesel engines including turbocharged vehicles.

Oil type		Fully-Synthetic
Pour point (°C)		-42.5
Flash point (°C)		234
Kinematic viscosity (mm²/s)	40°C	60.59
	100℃	10.29
Viscosity index		159



5W-40 SP/CF

Featuring the API license, this high performance oil provides superior engine protection while delivering improved fuel economy & engine cleaning. Recommended for both gasoline & diesel engines including turbocharged vehicles.

Oil type		Fully-Synthetic
Pour point (°C)		-40.0
Flash point (℃)		236
Kinematic viscosity (mm²/s)	40℃	80.07
	100℃	13.25
Viscosity index		168







