Version: 1.3 Date of issue: 2021/04/06



SAFETY DATA SHEET

1. Chemical Product and Company Identification

Product Name: AUTOBACS Fully Synthetic Diesel Engine Oil 5W-30 DL-1

Date of issue: 2021/04/06

Details of the supplier of the safety data sheet

: AUTOBACS SEVEN CO., LTD. Company

NBF Toyosu Canal Front, 6-52, Toyosu 5-Chome, Koto-ku, Address

Tokyo 135-8717, Japan

Name of Section : Overseas Business Department

: +81-3-6219-8779 TEL

Product Use : 4 Cycle Diesel Engine Oil

2. Hazards identification

[GHS LABEL ELEMENTS]

PHYSICO-CHEMICAL HAZARDS

No applicable GHS classification data.

HEALTH HAZARDS

No applicable GHS classification data.

ENVIRONMENTAL HAZARDS

No applicable GHS classification data.

FIGHS LABEL ELEMENTS

Pictogram

None

Signal Word : None Hazard Statement : None

Precautionary Statement

None

Other notes

: Even if there is no description in the precautionary statement based on GHS classification, sufficient consideration should be given to Safety measures / First aid measures / Storage / Disposal by referring to the

information in the following chapters.

3. Composition/information on ingredients

Substance or Preparation : Mixture

Component Content (%)

Mineral oil 90-100 Additive 5-10

4. First aid measures

AUTOBACS Fully Synthetic Diesel Engine Oil 5W-30 DL-1

Date of issue : 2021/04/06

Inhalation : If inhalation of mists, fumes or vapor causes irritation to

the nose or throat, or coughing, remove to fresh air.

comfortable for breathing.

: If symptoms persist obtain medical advice

Skin contact : Wash skin thoroughly with soap and water as soon as

reasonably practicable.

: If skin irritation occurs obtain medical advice.

Eye contact : Wash eye thoroughly with clean water.

: Obtain medical advice if any pain or redness develops or

persists.

Ingestion : If contamination of the mouth occurs, wash out thoroughly

with water.

Except as a deliberate act, the ingestion of large amounts of

product is unlikely. If it should occur, do not induce

vomiting; obtain medical advice.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health

effects and symptoms.

Necessary precautions for protection of person

performing first aid

measures

Special precautions for

doctors

: No information

: No information

5. Fire fighting measures

Extinguish media : Use foam, dry powder or water fog, carbon dioxide.

Extinguishing media that do

not use it

: Do not use water jets.

Specific hazards arising from the substance or

mixture

Fire Fighting : Eliminate all ignition sources if safe to do so.

: Water the surrounding equipment to cool them down.

: Cordon off the affected place and its vicinity to all,

except the concerned parties.

Specific protective

equipment for firefighters

: Keep upwind of fire. Wear full fire fighting turn-out gear

: Toxic fumes may be evolved on burning or exposure to heat.

See Section 10 for information on stability and reactivity.

(full Bunker gear) and respiratory protection (SCBA).

6. Accidental release measures

Personal precautions, protective equipment and emergency

: Use appropriate Personal Protective Equipment (PPE).

: Evacuate all non essential personnel from the immediate area.

Environmental precautions

: Prevent leakage into sewer, rivers and etc., and take

measures to prevent environmental pollution.

Methods and material for containment and cleaning up

: Absorb and recover by use of sand or other suitable inert

absorbent material.

Date of issue : 2021/04/06

: In a large leakage, enclose it with sand bank and stop outflow, and recover spilled material into containers. In event of spillage in the sea, extend oil fences to prevent diffusion, and sop up with absorbent materials. In event of using chemicals and/or detergents, they must satisfy the technical standards as set by the Ministry of Land, Infrastructure and Transport.

Prevention measure of secondary disaster

: In the case of large spills contact the appropriate

authorities.

: Promptly remove ignition sources nearby.

7. Handling and storage

Handling

Technical measures : Follow the regulations of the Fire Service Act.

: Keep away from flame or high temperature, and avoid, whenever

possible, a generation of vapor.

: Take measures against static discharge. Ensure to wear

clothing and shoes made of conductive materials.

: Never suck up (siphoning) this material by mouth.

Wear personal protective equipment if there exists a chance

of getting contact with skin or enter into eye.

: Do not breathe dust, vapor, spray.

Precautions : No information available

Precautions for safe : Perform

handling

: Perform local exhaust and general ventilation as described in

"8. Exposure controls/personal protection".

Avoid contact : Avoid contact with halogens, strong acids, alkali and

oxidizing materials.

Hygiene measures : Whilst using do not eat, drink or smoke.

: Wash hands thoroughly after contact.

Storage

Storage conditions : Store in a cool and well-ventilated place away from direct

sunlight.

: Keep container tightly closed

: Avoid heat, sparks, open flame and static accumulation.

: Label and display as hazardous material and store.

Safe container packaging

materials

: Do not pressurize empty containers. May cause rupture.

: Do not weld, heat up, drill or cut containers. May ignite the

residue and cause explosion.

8. Exposure controls / Personal protection

Control parameters

Chemical name

Administrative Japanese Society ACGIH levels of Occupational

Health

Mineral oil - 3mg/m3 TWA: 5mg/m3

Additive - - -

Date of issue: 2021/04/06

AUTOBACS Fully Synthetic Diesel Engine Oil 5W-30 DL-1

: Install the appropriate general ventilation equipment, local

exhaust ventilation in the workplace.

: Install eye shower and body shower near the work site.

Personal protection

Equipment

Respiratory protection : Use respiratory equipment appropriately in response to the

circumstances.

Hand protection : Use oil-proof protective hand gloves appropriately in

response to the circumstances.

Eye protection : Use safety glasses with side protection appropriately in

response to the circumstances.

Skin protection : Use protective clothing appropriately in response to the

circumstances.

Special precautions : No information

9. Physical and chemical properties

Physical state : Liquid

Color : Light brown Odor : Slight odor

Melting point : -42.5°C (Pour point)

Boiling point/Boiling range : No information available Flammability : No information available

Range of explosion (lower

bound - upper bound)

: 1-7vol%(estimated)

Flash point : 220° C (COC)

Autogenous ignition point : No information available

Decomposition temperature : No information available

pH : No information available

Kinematic viscosity : $57.6 \text{mm} 2/\text{s} (40^{\circ}\text{C})$ Solubility : Water: insoluble

Water partition coefficient : No information available
Vapor pressure : No information available

Density/Specific gravity : 0.85g/cm3(15°C)

Vapor density : No information available
Particle characteristics : No information available

Stability and reactivity

Reactivity: Stable under normal conditions of use and unlikely to react.

Chemical stability : Stable under normal storage conditions.

Possibility of hazardous

reactions

: No hazardous reaction known under conditions of normal use.

Conditions to avoid : Heat. Incompatible materials.

Incompatible materials : Halogens, strong acids, alkalies and oxidizing agents.

Hazardous decomposition

products

: Incomplete combustion/ thermal decomposition will generate smoke, carbon dioxide and hazardous gases, which will include

carbon monoxide.

11. Toxicological information

Version : 1.3

AUTOBACS Fully Synthetic Diesel Engine Oil 5W-30 DL-1

Date of issue : 2021/04/06

The hazard classification of products was classified based on the classification criteria of the mixture.

Acute toxicity(oral)

Mineral oil : Not classified LD50 > 5000mg/kg (Rat)

Acute toxicity(dermal)

Mineral oil : Not classified LD50 > 5000mg/kg (Rat)

Acute toxicity(inhalation: gases)

Mineral oil : Exempt classification

Acute toxicity(inhalation: vapors)

Mineral oil : Exempt classification

Acute toxicity(inhalation: dusts and mists)

Mineral oil : Not classified LC50 > 5mg/L (Rat 4h)

Skin corrosion/Skin irritation

Mineral oil : Not classified Prolonged or repeated skin contact as from

clothing wet with material may cause dermatitis.

Serious eye damage/Eye irritation

Mineral oil : Not classified Not expected to cause eye irritation.

Based on data from components or similar materials.

Respiratory sensitizer

Mineral oil : Classification not possible

Skin sensitizer

Mineral oil : Not classified No data available to indicate product or

components may be a skin sensitizer.

Germ cell mutagenicity

Mineral oil : Not classified No data available to indicate product or

components present at greater than 0.1% are mutagenic or

genotoxic.

Carcinogenicity

Mineral oil : Not classified The classification as a carcinogen need

not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex 1. The producer of "Lubricating oils" declares that it contains less than 3% DMSO extractable material by IP

346.

Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Toxic to reproduction/Effects on or via lactation

Mineral oil : Not classified/Not classified No data available to

indicate either product or components at greater than 0.1%

that may cause reproductive toxicity.

Specific target organ toxicity(single exposure)

Mineral oil : Not classified No data available to indicate product or

components present at greater than 0.1% that may cause

STOT by single exposure.

Specific target organ toxicity (repeated exposure)

AUTOBACS Fully Synthetic Diesel Engine Oil 5W-30 DL-1

Date of issue: 2021/04/06

: Not classified No data available to indicate product or Mineral oil

components present at greater than 0.1% that may cause

STOT repeated exposure.

Aspiration hazard

Mineral oil : Not classified

12. Ecological information

The hazard classification of products was classified based on the classification criteria of the mixture.

Hazard to the aquatic environment (acute)

Mineral oil : Not classified

Hazard to the aquatic environment (chronic)

Mineral oil : Not classified

Hazardous to the ozone layer

Mineral oil : Classification not possible

: Fathead minnow 96h LL50 > 100 mg/L Toxicity to fish

Fathead minnow 14d NOEL > 100 mg/L (Mineral oil)

: Crustacea (Daphnia magna) 48h EL50/NOEL > 10,000mg/L Toxicity to invertebrate

Crustacea (Daphnia magna) 21d NOEL > 10mg/L(Mineral oil)

Toxicity for algae : Selenastrum NOEL > 100 mg/L(Mineral oil) Persistence and : This product is not expected to be readily

degradability

biodegradable. (Mineral oil)

: No information available Bioaccumulative potential

Mobility in soil : Oil spilled on the surface may be adsorbed to the soil and is

unlikely to spill into groundwater. (Mineral oil)

13. Disposal considerations

: Dispose of via an authorized person/ licensed waste disposal Rest waste

contractor in accordance with local regulations.

: Be discarded in accordance with the standards of the local

government and relevant legislation.

: Incineration may be carried out under controlled conditions

provided that local regulations for emissions are met.

A pollution container,

packing

: When disposing of empty containers, after the contents have been completely removed, and the mixture is processed in accordance with the standards of the local government as well

as the related laws and regulations and waste disposal

method.

14. Transport information

UN Number No information available No information available Proper Shipping name No information available Class Packing Group No information available

Special safety measures for

transport or means of

transport

: Transport the container without significant friction or

agitation.

: Fire is strictly prohibited because of flammable liquid.

Version : 1.3

Date of issue: 2021/04/06

: A sign shall be displayed on the vehicle as specified by an Ordinance of the Ministry of Internal Affairs and Communications, and provide with fire fighting equipment, if and when required to transport more than the designated quantity for the vehicle.

Total piled height of vehicle shall be less than 3 meters for land transportation.

: Consolidation of this material with hazardous goods belonging to the Category I and Category VI is prohibited.

: Comply with applicable laws and regulations.

Domestic restriction

Land: Follow the transportation method specified by Fire Service

Act and Industrial Safety and Health Law.

Sea : Follow the transportation method specified by Ship Safety

Law.

Air : Follow the transportation method specified by Civil

Aeronautics Law.

15. Regulatory information

Fire Service Act : Category IV Inflammable liquids

Pollutant Release and Transfer Register (PRTR)

: Not Regulated

Industrial Safety and Health

Law

: Regulated

Poisonous and Deleterious Substances Control Law

: Not Regulated

Water Pollution Control Law : Regulated Sewage Control Law : Regulated

16. Other information

This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified below. We have reviewed any information contained herein which we received from sources outside AUTOBACS SEVEN. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license.

AUTOBACS SEVEN shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.